

UTENSIL POT WASHERS

MADISON IM65

code: 26-600







The IM65 commercial potwasher is designed to be ergonomically pleasing yet able to take care of the larger items found inside a kitchen. With a 650mm opening, it is ready to take on anything you are willing to throw at it.

FEATURES

- Warranty 1 year parts and labour, 3 years on the control board & cabinet (see p.28 for conditions & extended warranty offer)
- Energy Saving mode
- Automatic Detergent & Rinse Aid
- Self-Diagnostic system
- 2, 4, 6 & 12 minute wash cycle options
- · Low water consumption 4L per rack
- · Quick ready function
- Double skinned door

INCLUSIONS

- 1 x Generic steel basket 550mm x 610mm
- 1 x Drain hose
- 1 x Water connection hose
- 1 x Operating manual

TECHNICAL DATA			
He	Height		
Ca W	abinet abinet inc. legs ith hood extended sable Wash	1565 mm 1700-1760 mm 1975-2035 mm 630 mm	
Width			
Ca	abinet	720 mm	
De	epth		
-	abinet ith door open	780 mm 1180 mm	
Ca	apacities		
W Ri W Bo El El	pads/Hour later per Cycle lash Pump lash Pump lash Tank Litres liler Litres lement (wash) lement (rinse) letergent Injection lash Pump l	up to 30* 4L 1400W 200W 37 7 3000W 6000W yes yes	
Te	Temperatures		
	ash Degrees C nse Degrees C	60 °C 82 °C	
PI	umbing		
	ain ater	Gravity ¾" BSP (hot)	
El	ectrical		
	olts/Hz/Phase mps	400V/50Hz/3+N 16Amps/Ph	
* Subject to incoming water temperature			

^{*} Subject to incoming water temperature



Water pressure requirements are: 10L/min at 200-400 kPa max.