



## FED-X S/S Two Door Upright Freezer - XURF650S1V

### Quick Overview

- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm compatible shelves
- Self-closing lockable doors with heavy duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Ebm-papst evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- 1/2 split door system can lower yearly running cost by up to 30%

### Description

#### FED-X Stainless Steel Two Door Upright Freezer - XURF650S1V

- Net Capacity: 650L
- Cooling System: Fan forced cooling
- Temperature range: -18 to -22°C
- Compressor: Embraco/Secop
- Controller: Dixell
- Ambient Temperature: 43°C
- RH: 40%
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm compatible shelves
- Self-closing lockable doors with heavy duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Ebm-papst evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- 1/2 split door system can lower yearly running cost by up to 30%

2-Year Parts and Labour Warranty

## Specifications

---

<b>Net Weight (Kg)</b>	126
<b>Width (mm)</b>	740
<b>Depth (mm)</b>	830
<b>Height (mm)</b>	2000
<b>Packing Width (mm)</b>	765
<b>Packing Depth (mm)</b>	855
<b>Packing Height (mm)</b>	2070
<b>Power</b>	240V; 50V; 10A; 640W