


## MADISON IR200

code: 26-200



**Note: Shown with optional drying unit  
Left or Right Exit Available**

The high powered IR200 rack conveyor speeds through dirty crockery with ease with the ability to complete up to 200 racks per hour! This robust machine will ensure the busiest of work places become effective and efficient, cleaning perfectly time after time.

### FEATURES

- **Warranty** – 1 year parts and labour, 3 years on the control board & cabinet (see p.28 for conditions & extended warranty offer)
- Tank wash construction - deep drawn
- 2 x 1500W wash pumps
- Recirculating wash system
- 4 wash cycle options
- Double skinned door
- Left and Right hand exit available

### INCLUSIONS

- 1 x Plate rack 500mm x 500mm
- 1 x Flat rack 500mm x 500mm
- 1 x Cutlery container
- 1 x Drain hose
- 1 x Water connection hose
- 1 x Operating manual

Other bespoke rack conveyors available.

### TECHNICAL DATA

<b>Height</b>	
Cabinet	1420 mm
Cabinet inc. legs	1585-1645 mm
With door extended	2060-2445 mm
Usable Wash	430 mm
With dryer	1795-1855 mm
<b>Width</b>	
Cabinet	1971 mm
With dryer	2568 mm
<b>Depth</b>	
Cabinet	775 mm
<b>Capacities</b>	
Loads/Hour	up to 200*
Water per Cycle	270 L/hr
Wash Pump	1500W x 2
Rinse Pump	N/A
Wash Tank Litres	70 x 2
Rinse Tank Litres	17
Element (wash)	10500W
Element (rinse)	15500W
Detergent Injection	no
Rinse Aid Injection	no
<b>Temperatures</b>	
Wash Degrees C	60 °C
Rinse Degrees C	82 °C
<b>Plumbing</b>	
Drain	Gravity
Water	¾" BSP (hot)
<b>Electrical</b>	
Volts/Hz/Phase	400V/50Hz/3+N
Amps	40Amps/Ph
Note: 63 Amps with the dryer	

\* Subject to incoming water temperature

Water pressure requirements are: 10L/min at 200-400 kPa max.

