



# $\label{lem:url:lem:u$

### 7 Tray Blast Chiller - D-G7

#### **Quick Overview**

- Fast Blast Chiller features
- Built to HACCP specification
- · Stainless steel
- Special blast process prevents ice crystallisation from forming ensuring quicker temperature reduction
- Digital controller with probe and temperature display
- Ambient operating temp. 38°c
- European condenser and evaporating fans
- Fan-forced evaporator cooling
- · Auto defrost
- Self-evaporating drainage
- · Internal constructed for easy cleaning
- Self-closing doors

### 7 Tray blast chiller -Â D-G7

Description

Blast chilling and shock freezing are the best natural systems to extend the shelf life of food. Blast Chillers make it possible to lower the temperature at the core of foods that have just been cooked down to +3Â °C in less than 90 min. This reduces bacterial proliferation and dehydration of the food. The final result is the preservation of the quality, color and fragrance of the food, extending its shelf life. All this enables better service organization and reduced stress to the chefs, leaving more time for creativity.

They are ideal for commercial business that has a focus on quality, consistency and time management.

- Fast Blast Chiller features
- Built to HACCP specification
- Stainless steel
- Special blast process prevents ice crystallisation from forming ensuring quicker temperature reduction
- Digital controller with probe and temperature display
- Ambient operating temp. 38°c
- European condenser and evaporating fans
- · Fan-forced evaporator cooling
- Auto defrost
- Self-evaporating drainage
- · Internal constructed for easy cleaning
- Self-closing doors

Dimensions (WxDxH mm): Â 1250x800x850/95

1

Pan Capacity:Â 7x1/1GN

Chill temp range  $\hat{A}$  ° C: $\hat{A}$  20kg+70 to +3 in 90min

Deep Freeze temp. range ° C: 16kg +70 to -18 in 240min

Â

2 Years Parts and Labour Warranty

## Your Shipping Specifications

Net Weight (Kg)	300
Width (mm)	1250
Depth (mm)	800
Height (mm)	850/95
Packing Width (mm)	850
Packing Depth (mm)	1300
Packing Height (mm)	1000
Power	240V; 480/10 W/A