



URL: <https://www.foodequipment.com.au/media/catalog/product/p/t/ptd-601d.jpg>

## Axwood Passthrough Dishwasher 3 phase - PTD-601D

### Quick Overview

Axwood Pass-Through Dishwasher - Hood Type Dishwasher - PTD-601D

- Easy to use: Easy installation and service
- User- friendly one touch system
- High Performance: Powerful wash pump deliver higher volumes of wash water and ensures faster clean up times.
- Low running costs: Hi- tech computer controller ensures low water, low energy and less detergent consumption.
- Quality: Full stainless steel structure with stainless steel wash & rinse arms.
- Incoming water temperature 10-60Å ° C
- WaterMark approved

### Description

Axwood Pass-Through Dishwasher - Hood Type Dishwasher - PTD-601D

- Easy to use: Easy installation and service
- User- friendly one-touch system
- High Performance: Powerful wash pump delivers higher volumes of wash water and ensures faster clean up times.
- Low running costs: Hi-tech computer controller ensures low water, low energy, and less detergent consumption.
- Quality: Full stainless steel structure with stainless steel wash & rinse arms.
- Incoming water temperature 10-60Å ° C
- Rated currently of air circuit breaker 40A
- Record the number of washing 9999
- 60 racks per hour
- Drain outlet 42mm
- WaterMark approved

### Specifications

- Net Weight: 104kg
- Dimensions (WxDxH): 710 x 790 x 1430 ± 20 mm
- Door Entry: 400mm
- Basket Size: 500 x 500mm
- Electrical Supply (V/Hz/ph): N?415V AC / 50Hz / 3ph
- Cycle Length(3wash cycles): 60 / 90 / 120 sec

## Wash Pump, Tank and Element

- Wash Pump: 3-ph:400 L/min, 0.6 Kw
- Wash Tank Capacity: 27 Litres
- Wash Tank Heater :3.0 Kw
- Wash temperature: 60 ° C to 65 ° C

## Rinse Pump, Tank and Element

- Rinse Pump: 0.35 Kw
- Rinse Tank Capacity: 11 Litres  
Rinse Tank Heater: 9Kw
- Rinse Temperature: 82 ° C minimum
- Water Consumption: 2.9 Litres per cycle

## Electrical and Water Connections:

- Electrical Input: 415V / 50Hz / 3ph, 15.71Kw
- Water Input: 15 ° C minimum @ 100-400kPa
- Hot Water Inlet: 3/4 " B.S.P. fitting
- Drain Outlet: 1 1/2 " B.S.P. gravity fed

## 1 Year Parts and Labour Warranty

## Your Shipping Specifications

---

Net Weight (Kg)	104
Width (mm)	710
Depth (mm)	790
Height (mm)	1430
Packing Width (mm)	850
Packing Depth (mm)	745
Packing Height (mm)	1600
Power	415V / 50Hz / 3ph, 15.71Kw