



URL: <https://www.foodequipment.com.au/media/catalog/product/b/m/bm11td-bain-marie.jpg>

## BM11TD Heated Wet 6 x ½ Pan Bain Marie Angled Countertop Display

### Quick Overview

- Thermostat Control
- Easy To Clean
- Temp. Read-Out
- Drain Valves
- Air Insulated Tank With Double Skin Stainless Steel Construction In Satin Finish
- All Units Complete With Rear Sliding Doors On Rollers For Council Compliance
- In-Tank Temperature Probes For Accurate Measurement And Lower Running Costs
- Multiple Element Design For Reliable Operation And Even Temperature
- Improved Infra-Red Heat Lamp Configuration For Optimum Heat & Light
- Toughened Glass On All Sides For Maximum Safety
- Rectangular Base To Easily Drop In To Bench Cut-Out
- Optimum Visibility Of Product - No Unsightly Corner Post To Front
- Mechanical Thermostat Temperature Control
- Takes 6 x 1/2 Gastronorm Pans Up to 100mm Deep, Double row (Sold Separately)

\* 15A plug required

### Description

Heated Wet Six x ½ Pan Bain Marie Angled Countertop Display - BM11TD

All Stainless Steel

Heated: 35 to 85 °C

- Thermostat Control
- Easy To Clean
- Temp. Read-Out
- Drain Valves
- Air Insulated Tank With Double Skin Stainless Steel Construction In Satin Finish
- All Units Complete With Rear Sliding Doors On Rollers For Council Compliance
- In-Tank Temperature Probes For Accurate Measurement And Lower Running Costs
- Multiple Element Design For Reliable Operation And Even Temperature
- Improved Infra-Red Heat Lamp Configuration For Optimum Heat & Light

- Toughened Glass On All Sides For Maximum Safety
- Rectangular Base To Easily Drop In To Bench Cut-Out
- Optimum Visibility Of Product - No Unsightly Corner Post To Front
- Mechanical Thermostat Temperature Control
- Takes 6 × 1/2 Gastronorm Pans Up to 100mm Deep, Double row (Sold Separately)

\* Hot Food Holding Cabinets Only, Not Designed To Heat Product

\* 15A plug required

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration

Your Shipping Specifications

---

Net Weight (Kg)	38
Width (mm)	1060
Depth (mm)	630
Height (mm)	700
Packing Width (mm)	720
Packing Depth (mm)	1120
Packing Height (mm)	730
Power	15A; 240V; 2.5kW