



URL: <https://www.foodequipment.com.au/media/catalog/product/m/g/mg9-15bm-bain-marie.jpg>

Fagor Kore 900 Series Bain Marie Boiling Pan M-G915BM

Quick Overview

Tank: 600mm W x 500mm H Volume: 150L

- NG or LPG
- Surface tops manufactured in 2mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding and polishes. Screws hidden from view
- Double walled lid balanced by means of a hinge with front handle, with diagonal opening to 75° which allows the lid to be kept open in any position
- Well stamped into the surface top by robotic welding, manufactured in 304 S/S, with the bottom of the well in AISI-316L stainless steel.

Description

Fagor Kore 900 Bain Marie Boiling Pan M-G915BM

- NG or LPG
- Surface tops manufactured in 2mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding and polishes. Screws hidden from view
- Double walled lid balanced by means of a hinge with front handle, with diagonal opening to 75° which allows the lid to be kept open in any position
- Well stamped into the surface top by robotic welding, manufactured in 304 S/S, with the bottom of the well in AISI-316L stainless steel.
- Well filling with hot or cold water by electrovalve, activated with a single switch located on the front panel
- Well emptying by 2" safety valve with handle in athermic material and safe and effortless handling.
- Robust and reliable filter for draining the well manufactured in AISI-304 S/S. Easily extractable.
- Controls with protective base and system against water infiltration
- High temperature enameled cast iron flue protector.
- Access to the components from the front
- Machines with IPX5 grade water protection
- Group of optimised combustion stainless steel tubular burners, controlled by energy regulator and by pressure switch
- Control by energy regulator and by pressure switch, permitting lower water and energy consumption
- Ignition of group of burners by spark train

2 Year Parts and Labour + 2 Years Parts only Warranty with Product Registration

Your Shipping Specifications

Net Weight (Kg)	160
Width (mm)	800
Depth (mm)	930
Height (mm)	850
Packing Width (mm)	900
Packing Depth (mm)	1000
Packing Height (mm)	950
Power	86.4 MJ/hr ; 24 kW