



## Dito Sama Vegetable slicer single phase single speed 500w - TRS-500

### Quick Overview

Vegetable slicer, 1 speed 340 rpm, 500 W. Lever operated hopper in stainless steel for intense use

Performance (up to): 550 - kg/hour

URL: <https://www.foodequipment.com.au/media/catalog/product/t/r/trs-500.jpg>

### Description

TRS-500 Vegetable slicer single phase single speed 500w

- Performance (up to): 550 - kg/hour
- Suitable for 100-400 meals for table service and up to 800 meals for catering service.
- Vegetable slicer unit has slicing, grating, shredding (julienne) as well as dicing and french fries capabilities.
- Delivered with: [-] All stainless steel vegetable prep attachment with a lever-integrated long vegetable hopper (60mm diameter) and a large round hopper (215cm<sup>2</sup>)
- Ergonomically designed for right and left-handed users, frontal working and to reduce working space around the machine.
- All parts in contact with food are removable without the use of tools, stainless steel hopper, stainless steel lever and cutting chamber are dishwasher safe.
- Hopper easily removed for cleaning.
- Base inclined at 20 ° to provide easy loading and unloading.
- High discharge zone permits the use of deep GN containers (up to 20cm).
- Complete and wide selection of blades and grids available (diam. 205 mm).
- Pulse function for precise cutting.
- Magnetic safety system and motor brake. Prevents machine from running when lever swings away or is open.
- Automatic restart of the machine with the 3/4 moon shaped pusher in position.
- Continuous feed model.
- Red OFF, green ON buttons.

- Water protected planetary system (IP55 electrical controls, IP23 overall machine).
- All blades (available on request) are made in stainless steel and dishwasher safe.
- Power: 500 W - single or three-phase.
- 1 speed - 340 rpm - for precise cutting, slicing and dicing.
- Compact and portable design.
- Asynchronous silent industrial motor for heavy duty and longer life.
- Feeding arm and hopper are made entirely in stainless steel. Aluminum motor housing.

2 Years Return to Base Warranty

Your Shipping Specifications

---

Net Weight (Kg)	12
Width (mm)	216
Depth (mm)	347
Height (mm)	412
Packing Width (mm)	300
Packing Depth (mm)	600
Packing Height (mm)	500
Power	230 V/1N ph/50 Hz 250kW